



HEATING & AIR CONDITIONING EQUIPMENT

R410A-B

An Ideal Degree of Comfort for All Types of Multi-Family Construction

COMFORT PACK CPE-series

Electric Heat - Electric Cooling

FEATURES

- Totally Self-Contained Heating and Cooling Units
- 1 to 2.5 Ton Cooling Capacities
- Easy, Reachable Access Ports
- Up to 51,000 BTUH Heating Capacity Output
- Completely Precharged and Prewired
- Slide Out Chassis
- Totally Polarized Molex Electrical Plug Connections on Cooling Chassis
- Supplied with Pre-Painted Stamped Exterior Grille
- 16" x 25" Filter Included

COOLING SYSTEM

- R-410A High Efficiency Compressor
- Copper Tube with Enhanced Aluminum Fin Coils
- Permanently Lubricated, High Efficiency PSC Motor

HEATING

- Up to 15KW Electric Resistance Heat
- Fast-Acting Open Wire Elements
- Internal Automatic Reset Thermal Limits
- One-Stage Heat Control with Sequenced Steps
- Internal Fusing

MEETS 2010 DOE REQUIREMENTS FOR ALL UNITS.

Thru-the-Wall Comfort Pack units with heating capacities up to 15 KW. Cooling capacities from 1 to 2.5 tons.



Applications include: high-rise condominiums, garden apartments, retirement villages, luxury town homes, hotels and motel suites, and student housing.

WE GO THRU-THE-WALL™

COMFORT PACK Electric Heating - Electric Cooling

ELECTRICAL DATA

MODEL	VOLTAGE	COMPRESSOR		INDOOR BLOWER MOTOR		OUTDOOR FAN MOTOR		TOTAL AMPS	MINIMUM CIRCUIT AMPACITY	MAXIMUM OVERCURRENT PROTECTOR
		RLA	FLA	HP	FLA	HP	FLA			
CPE41205-BT	208-230/60/1	5.4	28.0	1/4	1.1	1/4	1.8	24.2	30.3	35
CPE41210-B	208-230/60/1	5.4	28.0	1/4	1.1	1/4	1.8	46.0	57.5	60
CPE41805-B	208-230/60/1	6.5	43.0	1/4	1.1	1/4	1.8	24.2	30.3	35
CPE41810-BT	208-230/60/1	6.5	43.0	1/4	1.1	1/4	1.8	46.0	57.5	60
CPE41815-B	208-230/60/1	6.5	43.0	1/4	1.1	1/4	1.8	67.8	84.6	90
CPE42405-B	208-230/60/1	9.9	54.0	1/4	1.8	1/4	1.8	24.2	30.3	35
CPE42410-B	208-230/60/1	9.9	54.0	1/4	1.8	1/4	1.8	46.0	57.5	60
CPE42415-B	208-230/60/1	9.9	54.0	1/4	1.8	1/4	1.8	67.8	84.6	90
CPE43010-B	208-230/60/1	10.6	54.0	1/3	2.3	1/4	1.8	46.0	57.5	60
CPE43015-B	208-230/60/1	10.6	54.0	1/3	2.3	1/4	1.8	67.8	84.6	90




PERFORMANCE DATA

MODEL	COOLING BTUH	HEATING BTU @ 230V	EER (outside temp.)		HEATING KW	SHIP WT.
			82°	95°		
CPE41205-B	12,000	17,000	11.0	9.0	5	315
CPE41210-B	12,000	34,000	11.0	9.0	10	315
CPE41805-B	18,000	17,000	11.0	9.0	5	325
CPE41810-B	18,000	34,000	11.0	9.0	10	325
CPE41815-B	18,000	51,000	11.0	9.0	15	325
CPE42405-B	23,600	17,000	11.0	9.0	5	350
CPE42410-B	23,600	34,000	11.0	9.0	10	350
CPE42415-B	23,600	51,000	11.0	9.0	15	350
CPE43010-B	27,500	34,000	11.0	9.0	10	360

OPTIONAL ACCESSORIES

CPWS	WALL SLEEVE (UNASSEMBLED)
CPWSA	WALL SLEEVE ADAPTOR (UNASSEMBLED)
CPLG	ARCHITECTURAL LOUVER GRILLE
CPLG-S	ARCHITECTURAL LOUVER SLEEVE GRILLE
CPLG-P	ARCHITECTURAL LOUVER GRILLE (PAINTED)
CPLG-SP	ARCHITECTURAL LOUVER SLEEVE GRILLE (PAINTED)
PAINTED LOUVER	STAMPED GRILLE (PAINTED)
-BF (CALL FOR DETAILS)	SLOTTED FILTER DOOR
-BD (CALL FOR DETAILS)	SECONDARY DRAIN PAN
-BP (CALL FOR DETAILS)	OMITED STAMPED LOUVER AND GRILLE
-BB (CALL FOR DETAILS)	COMBINATION OF (-BD) AND (-BP) SEE ABOVE CONSULT FACTORY FOR OTHER COMBINATIONS

Note: All specifications are subject to change without notice.



Option (BF)
Slotted Filter Door
for Open Returns



National Comfort Products offers Architectural Louver Grilles for all models. Outdoor grilles provided by others must be approved by National Comfort Products to maintain unit performance and warranty coverage. See Architectural Louvered Grilles Specification Sheet for more details.



A Division of National Refrigeration and Air Conditioning Products, Inc.
539 Dunksferry Road • Bensalem, PA 19020
(800) 523-7138 • Phone (215) 244-1400
Fax (215) 639-1674
www.nationalcomfortproducts.com